

FREWITT **F**

FLEXMILL CRUSHER CC-2

MORE THAN A CRUSHER



WE
CARE
ABOUT
MILLING

WWW.FREWITT.COM



This technology is patented and owned by Frewitt. Any infringement of our rights will be subject to immediate legal action.

FLEXMILL CRUSHER CC-2

Over the years, Frewitt has proven itself as the market leader in the field of powder milling machines. In its factories, Frewitt develops and produces high-quality mills. Frewitt is the ideal and most qualified partner for your solutions, our broad spectrum of competence will cover all your needs.

WHY CHOOSE FREWITT?

1

Provides solutions to your problems of line blockages, during production, due to hard and large blocks

2

Solutions that will optimize your production time and increase the quality of grinding

3

Optimized investment with anticipation of your future needs

4

Designed to ensure your safety

5

Machine developed with our commitment
FREWITT CARES ABOUT YOU

ADDED-VALUE

Module



- Unique solution on the market with crushing zone covering the entire discharge surface
- Simplified disassembly, assembly and cleaning
- Compact assembly for easy in-line integration
- Module or complete machine

Machine



- Possibility to mill with a high throughput
- Compatible with all Frewitt machines
- Integrated system to avoid product bridging
- High-tech process bearing
- Fixation of the module either directly by the frame or supported by the motor



SUITABLE FOR THE FOLLOWING INDUSTRIES:



Pharmaceutical



Battery



Chemical



Food

PROCESS CHARACTERISTICS




Maximum product size at the inlet
150mm



Throughput
10 to 8000 kg/h



Temperature range of product
-20°C to +60°C



Product density
up to 2.5 kg/dm³

TECHNICAL CHARACTERISTICS



Materials

AISI 316/316L - Ra ≤ 0.8 μm
AISI 304/304L - Ra ≤ 1.4 μm
EPDM/PTFE/Silicone

Interior
Exterior
In product contact,
certified FDA



Dimensions & weight

| Module | | Machine | |
|--------|--------|---------|---------|
| Length | 710 mm | Length | 1400 mm |
| Width | 420 mm | Width | 870 mm |
| Height | 440 mm | Height | 1900 mm |
| Weight | 110 kg | Weight | 280 kg |

Diameter DN250



Standard

GMP
Sealed process
Speed control
High throughput
Integrated
bridge-breaker



Optional

Bearing temperature
measure
Ventilated bearing
Specific custom tooling
ATEX
WIP
SIP



WORLDWIDE PRESENCE



FREWITT HEADQUARTERS

Frewitt manufacturer of machines Ltd.

Route du Coteau 7
1763 Granges-Paccot
Switzerland

Postal address

P.O. Box
1701 Fribourg
Switzerland

P: +41 26 460 74 00
info@frewitt.com
www.frewitt.com

**Frewitt Pharma Machinery
(China) Co. Ltd.**

1029 Shenfu Road,
Xinzhuang Industrial Zone
201108 Shanghai
China

P: +86 21 548 32950
info@frewitt-china.cn
www.frewitt-china.cn

Frewitt USA, Inc.

249 Homestead Road,
Building 5, Unit 8
Hillsborough, NJ 08844
USA

P: +1 908 829 5245
info@frewitt-usa.com
www.frewitt-usa.com